



laundry equipment

Drying cabinet

DC 4



FEATURES

- Flexible construction allows hanging bars to slide easely forward for easy access to garments or down for more space.
- Easy to install; the evacuating channel is connected to the ventilation system and the humid air is transported out of the room.
- All electrical components are placed on the top which makes it easy to maintain.
- Pull-out hanging system
- 3 temperatures; high, normal, low
- Energy efficient
- Timer ajustible up to 4 hours
- Overheat protection
- IP 24 classification. CE-approved
- The door can be ordered right- or left-hanged

OPTIONS

- Baskets to drip dry on a flat surface
- Hangers for small items (door frame)

MARKETS

Day care center, Schools, Road workers dressing room, Ships, Airports, Ski resorts, Campings, Security

Main specifications		DC4
Loading capacity	kg/lbs	4 kg/8,8 lbs
Drying capacity	g/min*	17
Hanging length	m/feet	16/52,5
Drying time, economy 30° C	min*	180
Drying time, express 45° C	min*	120
Heating effect	kW	1,5
Total effect	kW	1,535
Energy consumption economy /kg	kWh	0,5
Energy consumption express /kg	kWh	0,6
*Valid for high-spinned textiles.		

Technical specification		DC4
ELECTRICAL CONNECTIONS		
Electrical connection		1N, 230 V, 50 Hz
Fuse	А	10
Total effect	kW	1,535
Heating elements	kW	1,5
AIR CONNECTIONS		
Outlet exhaust	ø mm/inch	100/3,94
Outlet air flow	m³/h	50
Pressure drop	max Pa	60
Dewatering capacity	g/min	17
SOUND LEVEL		
Airborne sound level	dB(A)	60
SHIPPING DATA		
Net	kg/lbs	61/134,5
Crated	kg/lbs	4/8,8
Shipping data net	kg/lbs	65/143
Shipping volume	m ³	0,2
OPTIONAL EXTRAS		
Air exchanger 1 vent.,		
125 mm/4,9 inch	part number	141009
Air exchanger 2 vent.,		
160 mm/6,3 inch	part number	141018
DIMENSIONS		
Width	mm/inch	595/23,4
Depth	mm/inch	615/24,2
Height	mm/inch	1915/75,4